

Mixing

X-Shield FlexCoat is supplied as a two component pack consisting of filler and liquid polymer. Both components are pre-measured and no addition of water is necessary. Place the liquid polymer component into a suitable container and slowly add the filler component while mixing with a slow speed drill fitted with an approved mixing paddle. Mix for approximately 3 minutes until a lump-free creamy consistency is achieved. Mix only sufficient material for application within 45 minutes.

Application

Apply using brush, roller or hopper spray. First coat should be applied at 1 liter per m²; subsequent coats at 0.5 to 1.0 liter per m². Apply subsequent coats once the coat beneath has dried. The coating can be reinforced using X-Shield Reinforcing Fabric, X-Shield CrackMat or X-Pruf Roof Scrim.

Limitations

Do not add water to the material.
Temperature of the mixed coating should be less than 30C at time of application.
Do not apply to substrates that have free water on them.
Do not water test until the coating has cured for 7 days. Do not immerse until the coating has cured for 7 days. Not suitable for use with acids.
Do not apply below 5C.
Avoid excessive application.
Avoid skin contact.
Do not discard into the water system.

Health and Safety

This product is for industrial use only by trained operatives. It is potentially hazardous if not used correctly. Please refer to the Material Safety Data Sheet (MSDS) prior to the purchase and use of this product. The MSDS can be obtained via our website www.ncc.com.eg.

Authorized Technical Specialist

Please note that only NCC X-Calibur Authorized Technical Specialists ('ATSSo are permitted to change any of the information in this data sheet or to provide written recommendations concerning the use of this product. Visit www.ncc.com.eg for a full list of NCC X-Calibur ATSS.

Datasheet Validity

NCC X-Calibur makes modifications to its product datasheets on a continuous basis. Please check the datasheet update section on www.ncc.com.eg to ensure you have the latest version.

Warranties

NCC X-Calibur supplies products that comply with the properties shown on the current datasheets. In the unlikely event that products supplied are proved not to comply with these properties, then we will replace the non-compliant product or refund the purchase price. NCC X-Calibur does not warrant or guarantee the installation of the products as it does not have control over the installation or end use of the products. Any suspected defects must be reported to NCC X-Calibur in writing within five working days of being detected. NCC X-Calibur Construction Chemistry. **makes no warranty as to merchantability or fitness for a particular purpose and this warranty is in lieu of all other warranties express or implied.** NCC X-Calibur Construction Chemistry. shall not be liable for damages of any sort including remote or consequential damages, down time, or delay.



Quality Statement

All Products manufactured by NCC X-CALIBUR or imported from X-CALIBUR companies world-wide are manufactured to procedures certified to conform the quality, environment, systems described in the ISO 14001:2004. ISO 9001:2000.



Hotline: 16960

E-mail: Info@ncc.com.eg

Website: www.ncc.com.eg

www.x-calibur.us